

## Multimedia Player



AVStore presenta il primo player multimediale per applicazioni di digital signage e informazione al pubblico dedicato ai professionisti della comunicazione digitale. Nessun sistema operativo commerciale da riavviare, nessun hard-disk da sostituire: ecco una macchina realmente "plug-and-play". Finalmente un dispositivo robusto e affidabile per creare sistemi di videocomunicazione di alta qualità e a basso costo di manutenzione.



### Specifiche tecniche

#### CONTENUTI MULTIMEDIALI

Content description language SVG Tiny 1.2 + (Scalable Vector Graphics)

Media/animation synchronization SMIL 2.1

Still image formats JPEG, PNG, GIF, SVG

Supported video codecs ISO MPEG1, MPEG2, MPEG4 ASP (DivX), MJPEG, Microsoft VC1 (Windows Media Video 9)

Supported audio codecs ISO MPEG Audio layer 1/2/3 (MP3), ITU G.711, G.722, G.729, PCM, Microsoft WMA, Real Audio

Media container formats AVI, ASF/WMV/WMA, VOB, AIFF, OGG, WAV

Streaming media protocol MMS, RTSP, RTP, SDP, HTTP

Import filters provided for Microsoft PowerPoint presentations, BMP, TIFF, XPM, WBMP, PNM bitmaps

Content scripting language PHP 5

Content scheduling iCalendar (RFC2445)

#### VIDEO

Aspect ratio 16:9, 16:10, 4:3

Maximum resolution 1280x720 (16:9), 1024x640 (16:10), 1024x768 (4:3)

Video standards HD-Ready: 480p, 576p, 720p, 50 or 60 fps

#### NETWORK

Connectivity Ethernet 10/100 Mbit/s, IEEE 802.3u, 802.3x

Protocols IPv4, DHCP or fixed address

Remote configuration HTTP configuration server, password protected

Content administration WebDAV server, password protected

Other protocols SNMPv1/v2c, NTP

#### CARATTERISTICHE FISICHE

Size 105mm (W) x 83mm (D) x 26mm (H) / 4.13' (W) x 3.27' (D) x 1.02' (H)

Weight 190g / 6.7 oz

Power supply 5V DC, typ. 0.4A (2W)

Power supply input 100-240V 50-60 Hz, max input current 0.6A

Operating temperature 10 to 35 °C (50 to 95 °F), 10 to 90 % RH

Storage temperature -25 to 45 °C (-13 to 113 °F), 10 to 90% RH

Real time clock Min accuracy 1 min / month free running, battery backed

#### CONNECTIVITY

External storage USB 2.0 Hi-Speed, one port. Supports USB flash and hard drives

Serial RS232, up to 115200 bauds, mini-jack 3.5mm

Network RJ-45 Ethernet

Video output HDMI (inc. digital audio), DVI via adapter. VGA (DB15 HD connector)

Analog audio output Line level, stereo, mini-jack 3.5mm

#### GARANZIA

Copertura a vita sull'hardware



#### AVstore

www.avstore.tv

info@avstore.tv

via Baracca, 17  
Brugherio (Mi)  
Italy

Ph. 039 21.84.368

Fx. 039 28.76.554